



Cyclops Multi-Point Awning / Casement Window

Heavy duty and built to last, the Cyclops Multi-Point Awning / Casement Window is capable of withstanding cyclonic wind conditions. Concealed multi-point operable fixings offer supreme durability, converting a basic awning / casement window into a fixed and secured glass panel. Cyclops can be retrofitted to most standard awning / casement windows available in the market today – including pre-existing fixtures. Cyclops has been tested to withstand extreme weather conditions, including 360 km/hr winds and 800pa water penetration resistance.



FEATURES & BENEFITS

- Concealed fixings with one handle able to operate several locking points
- Retrofits to existing awnings
- Smooth lining and edging
- Cast corners to ensure fast, precise and secure assembly
- State-of-the-art Santoprene Ezi-Seal technology
- Continuous top hinge – secures sash and provides extreme weather durability
- Enhanced air ventilation



PRODUCT OPTIONS

- Single, double, or high-impact glazed sash options
- Snap-in adaptor sections for modular configurations
- Key-lockable chain winders
- Ezi-Fit security or fly screen provision

WINDOW ENERGY RATING - TOTAL WINDOW AFRC

Window ID	Glazing	Uw	SHGC	Tvw	Air Inf.
Single Glazing					
EZI-011-01	6.38mm Clear Laminate	6.3	0.58	0.62	0.17
EZI-011-02	6.38mm Grey Laminate	6.3	0.47	0.30	0.17
EZI-011-03	6.38mm Comfort Plus Grey	4.9	0.39	0.28	0.17
Double Glazing					
EZI-031-01	6mm Clear / 12mm Air / 6mm Clear	4.4	0.40	0.37	0.17
EZI-031-02	6.38mm ComfortPlus Grey / 12mm Air / 6mm Clear	4.0	0.31	0.23	0.17
EZI-031-03	6.38mm ComfortPlus Clear / 12mm Argon / 6mm Clear	3.9	0.43	0.49	0.17

SPECIFICATIONS

FRAME SIZE

50mm, 65mm, 100mm,
101.6mm, 150mm

MAXIMUM SASH HEIGHT

1800mm

MAXIMUM SASH WIDTH

1800mm

MAXIMUM SASH WEIGHT

50kgs

MAXIMUM NO. OF SASHES

Unlimited

GLAZING RANGE

4mm - 8.38mm (12.5mm pocket)
10.38mm - 15mm (18.5mm pocket)
15mm - 32mm (35.2mm pocket)